

HP Atalla Ax150 Network Security Processors

Data sheet



The high-performance Atalla Ax150 Network Security Processors, an evolution of the industry-leading Atalla Ax100 NSP family, provide the fastest and most secure hardware-based cryptographic processing for ATM/EFT/POS networks.

HP Atalla Ax150 series network security processors (NSPs) provide unrivaled protection for Triple DES and other cryptographic keys when safeguarding value-based transactions. They are designed as the hardware complement to the Atalla Key Block, the industry-standard advanced key management solution.

The Atalla Ax150 series NSPs consist of three models. Each model offers identical security functionality, with different processing capabilities:

- **Atalla A10150 NSP.** At 990 PIN translates per second when used with the Atalla Key Block, the A10150 NSP efficiently handles high-volume environments and delivers the fastest and most secure Triple DES performance on the market.
- **Atalla A9150 NSP.** At 220 PIN translates per second, the A9150 NSP is a cost-effective solution for mid-level transaction environments, providing exceptional security and functionality.
- **Atalla A8150 NSP.** At 60 PIN translates per second, the A8150 NSP works well in low-volume transaction environments and has all the security and functionality of larger NSP models. It is the first entry-level device to provide both an auto-sensing Ethernet interface for fast host connectivity and an asynchronous interface for compatibility with legacy systems.

Features at a glance

- Industry-leading physical and logical security
- Advanced Atalla Key Block for optimal Triple DES key management
- Plug-and-play fast host connectivity
- Superior flexibility and ease of use
- Space-saving, state-of-the-art, rack-mountable platform
- Command-set compatibility with all previous Atalla network security processors
- Easy firmware upgrades via the Atalla Ax150 CD-ROM

Institutions can match their security processors to their particular throughput demands, while gaining the ability to scale gracefully when necessary without changing their applications.

From a hardened, rack-mountable, 2U perimeter to a state-of-the-art tamper-resistant architecture to secure remote key loading, the Atalla Ax150 NSPs raise the bar for physical and logical security, flexibility, and ease of use. They also interoperate transparently with non-Atalla hardware security modules. As an optimal platform for the industry-standard Atalla Key Block, the Atalla Ax150 NSPs enable you to derive the full security value of single-length DES, two- and three-key Triple DES, and public key encryption—alone or in a mixed encryption environment—while providing a cost-effective migration path to even stronger future algorithms.

The new-generation Atalla Ax150 NSPs incorporate more than three decades of standards-based cryptographic expertise coupled with the latest open systems technologies from HP—making the Atalla Ax150 NSPs the fastest, safest security processor solution for your ATM/EFT/POS networks.



Optimal key management with the Atalla Key Block

The Atalla Key Block is the advanced key management complement to the Atalla Ax150 NSPs and other Atalla NSP models. The Atalla Key Block has been embraced by leading financial industry ISVs and adopted as part of the industry standard ANSI X9.24 Part 1-2004, Retail Financial Services Symmetric Key Management Part 1: Using Symmetric Techniques. Together, the Atalla Key Block and Atalla Ax150 NSPs offer these benefits:

- A single solution with simultaneous support for single-length DES and two- and three-key Triple DES keys, public keys, and others
- Support for future algorithms, key types, and key lengths
- Fully secure mixed encryption environments (with masking of weaker keys)
- Full hardware and software investment protection far into the future

Physical security

- FIPS 140-2 Level 4 certification for physical security
- Rack-mountable (2U), physically fortified form factor
- Double-locking bezel with Medeco locks
- Penetration protection (protective grid)
- Out-of-range temperature and voltage detection
- Low battery voltage protection
- PIN security and key management implemented within a secure hardware perimeter for protection against manipulation

Logical security

- FIPS 140-2 Level 4 certification for key management
- Industry-standard Atalla Key Block key management technology
- Advanced security architecture that prevents retrieval of PIN, keys, and other sensitive data in cleartext form
- Automated and manual key management options
- Encrypted, convenient configuration, management, and key loading via the Atalla Secure Configuration Assistant (no cleartext passing of keys or key components)
- Remote ATM key initialization and re-keying via the optional Atalla Remote Key feature

Performance

- Benchmarked at up to 990 Triple DES PIN translates per second using the Atalla Key Block
- Tailored to entry-level, mid-level, or high-volume environments to meet processing performance needs and demanding security requirements
- Linear performance scaling with additional units

Fast host connectivity

- Auto-sensing 10/100/1000Base-T Ethernet interface for point-to-point TCP/IP
- Integrated high-performance TCP/IP stack and communications processor
- Asynchronous connection for legacy applications also supported by the Atalla A8150 NSP



Flexibility and extensibility

- Broad application support (ATM/EFT/POS, stored value, loyalty cards, corporate funds transfer)
- Customer-defined security policies enforced
- Easy command set customization
- Seamless interoperability with non-Atalla environments
- Atalla Remote Key support for initiatives from NCR, Diebold, and other ATM vendors
- Command set compatibility with earlier models of Atalla NSPs

Easy to use and manage

- Encrypted, convenient key loading via the Atalla Secure Configuration Assistant
- Simple-to-use GUI for Atalla Key Block key loading
- Fast, convenient release upgrades via CD-ROM
- No need to replace firmware components (for example, EPROM) when upgrading

Support for most standards

- Cryptographic support
 - Data Encryption Algorithm (DEA) standard (ANSI X3.92-1987, ISO 10126-2), DES, and two- and three-key Triple DES
 - Banking Procedures for Message Encipherment, General Principles (ISO 10126-2)
 - PIN Management and Security, Part 1 and 2 (ANSI X9.8, ISO 9564-1 and 2)
 - Message authentication (ANSI X9.9-1987, ISO 9807)
 - MasterCard CVC (Card Validation Code), Visa CVV (Card Verification Value), and American Express CSC (Card Security Code)

- Unique key per transaction (ANSI X9.24-1990)

- EMV-based smart card support

- PIN verification methods

- Atalla Identikey

- IBM 3624

- Visa PVV (PIN Verification Value)

- Atalla Bi-Level DES

- Diebold

- NCR

- PIN block formats

- ANSI X9.8-1982

- PIN Pad

- IBM 324 ATM PIN format

- Unisys (Burroughs)

- Diebold

- Docutel/Olivetti

- Visa Derived Unique Key Per Transaction

- Key management standards

- ANSI X9.17-1985

- ANSI X9.24-2004

- ANSI X9.52

Global support

HP provides worldwide support and services to ensure a secure business environment.

HP Atalla Ax150 Network Security Processors

Ordering information

Product ID	Description
T16/A10150	Atalla A10150 network security processor with Atalla Key Block
T16/A10150V	Atalla A10150 network security processor with variant key management
T16/A9150	Atalla A9150 network security processor with Atalla Key Block
T16/A9150V	Atalla A9150 network security processor with variant key management
T16/A8150	Atalla A8150 network security processor with Atalla Key Block
T16/A8150V	Atalla A8150 network security processor with variant key management
T16/ARKEY	Atalla Remote Key feature

Specifications

Physical dimensions

Height	8.71 cm (3.43 in)
Width	48.49 cm (19.25 in)
Depth	74.29 cm (29.25 in)
Weight	23.75 kg (57.35 lbs) no drives

Controls

Power on/off switch

Electrical

Dual input voltage, autosensing	100–120 V AC at 3 A, 50–60 Hz; 200–240 V AC at 1.5 A, 50–60 Hz
Power consumption	120 V AC at 1.8 A, average; 3.25 A maximum at power on

Operating environment

Temperature	10°–35° C (50° to 95° F)
Relative humidity	10% to 90% noncondensing 45° C

Certification/compliance

Safety	ULC, CE, TUV approved
Emissions	FCC, C-Tick, Gost
Environmental	RoHS

Connectivity

Communications	Ethernet running TCP/IP
Connection	10/100/1000Base-T (RJ45) auto-sensing Additional asynchronous connection for the Atalla A8150 NSP

© 2006 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information visit www.hp.com/go/atalla

September 2006

